



Inspection Manual Addendum

Inspection Location Standards document reference 08.18/MC

Issue date:

Effective date	Page No.	Section	Change to manual	Change to inspection forms	Comments
4 th December 2017	16	6.3	<p>In requirements, add a section following the bullet point 'marked with its next test date (month, year)'</p> <p>Each fire extinguisher container is:</p> <ul style="list-style-type: none"> • Accessible and suitably labelled • Weather proof with a secure lid/door • Securely mounted and free from damage 	<p>All three forms, amend 6.3 first line to read: Is its stowage accessible, weather proof, secure lid/door, securely mounted, suitably labelled and free from damage</p>	To clarify the requirements of the fire extinguisher container
4 th December 2017	16	6.3	<p>In reason for failure, add the following sections after '(maximum 12 months period)'</p> <p>Extinguisher container not accessible, suitably labelled, weather proof, secure or free from damage</p> <p>The combined extinguisher capacities do not meet the minimum total requirements, or do not meet the minimum individual requirements (see note)</p>	See above	Clarifying the requirements of the fire extinguisher container and capacities to accommodate operational situations
4 th December 2017	16	6.3	<p>In requirements amend the following:</p> <p>Note: the minimum capacities for fire extinguishers are:</p> <ul style="list-style-type: none"> • at least one 6kg (minimum) outside the cab • at least one 2kg (minimum) for the cab 	None	Clarifying the requirements of the fire extinguisher capacities to accommodate operational situations



Inspection Manual Addendum

			<ul style="list-style-type: none"> • 12kg (minimum) in total <p>To read:</p> <p>Note: the minimum capacities for fire extinguishers are:</p> <ul style="list-style-type: none"> • External - at least one 6kg (minimum) • Cab - at least one 2kg (minimum) • Total capacity per tractor/trailer or rigid chassis - 12kg (minimum) 		
4 th December 2017	16	6.3	<p>Amend and add to the note to read: Where an external fire extinguisher container is fitted to a tractor, trailer or chassis, it should contain a serviceable fire extinguisher of at least 6kg capacity (or equivalent). Where:</p> <ul style="list-style-type: none"> • a tractor is presented for inspection without a trailer, only the cab requirements are applicable • a trailer is presented for inspection without a tractor, only the external requirements are applicable • a rigid chassis is presented for inspection, both the cab and external requirements are applicable 	None	Clarifying the requirements of the fire extinguisher capacities to accommodate operational situations
5 th January 2018	26	11.2	<p>Amend the second reason for failure to read: Drain tube fitted with a valve capable of being closed</p>	None	To provide clarification on drain tube valves
5 th January 2018	4	1.2	<p>Amend the reason for failure to read: Vapour tightness test certificate not presented, or is not valid/expired</p>	None	To provide clarification on presence of certificate